

CALIWEL™ with BNA™
Antimicrobial* HVAC Covering

Caliwel is a coating that employs a natural antimicrobial agent - **calcium hydroxide** - to protect the coating from odor and stain causing microorganisms for years after it is applied.

<u>TECHNICAL DATA</u>	<u>SPECIFICATIONS</u>	<u>SURFACE PREPARATION</u>
<p>Recommended HVAC Applications:</p> <ul style="list-style-type: none"> • Healthcare Facilities • Eldercare Facilities • Educational Facilities • Residential Interiors • Manufacturing Facilities • Warehouse Facilities <p>Suitable Substrates:</p> <ul style="list-style-type: none"> • Metal <p>Colors: Industrial standard; customs</p> <p>Coverage: 250 sq ft/gallon @ 2 mills dry</p> <p>Dry Time @ 70°F, 50% RH: Touch: 15 minutes Recoat: 4 hours</p> <p>Flame Spread and Surface Burning (ASTM E84): Surface tested: Cement board and Red oak</p> <p>Max. temp: 560°F Flame Spread Index (FSI): 0 Smoke Developed Index (SDI): 0</p> <p>Finish: Flat</p> <p>Vehicle Type: Latex</p> <p>VOC: 0.2 gms/L</p> <p>Weight/Gallon: 11.25 lbs</p> <p>Storage Temperature: Minimum: 45°F Maximum: 120°F (45 days max)</p>	<p>HVAC Ductwork Surfaces 1 or 2 coats – Caliwel</p> <p>Avoid aluminum, plastic, glass</p>	<p>Mold/Mildew On Surface – scrape/remove all loose material.</p> <p>Previously Painted Surfaces – remove all loose paint, dirt, chalk and damaged substrate. Clean thoroughly to remove wax, grease and/or oil residue. Scuff-sand glossy surfaces. Wipe with a clean damp rag to remove sanding dust. Stains from water, smoke, grease, ink, etc. must be sealed with a suitable stain-blocking primer.</p>

* Caliwel contains an antimicrobial active ingredient – Calcium hydroxide – that protects both the liquid coating and the dried coating’s surface.

<u>APPLICATION</u>	<u>CLEAN UP</u>	<u>SAFETY INFORMATION</u>
<p>For interior walls of HVAC use only.</p> <p>Apply at surface temperatures between 55°F and 100°F. For the best results apply Caliwel at about 75°F.</p> <p>Surface must be dry and at least 5°F above dew point.</p> <p>Reducer: DO NOT MIX WITH TAP WATER OR ADD PAINT OR PAINT THINNERS. Such action may adversely impact biocidal properties.</p> <p>Reduction: Maximum 5% with water</p> <p>Avoid aluminum parts in sprayer.</p> <p>Product is best applied by airless sprayer. Avoid use of sponge roller or sponge brush. Due to rapid dry time of coating, only small areas should be brushed or rolled. CAUTION! When spraying, wear goggles and a high-efficiency particulate respirator. Caution-off the immediate application area to prevent others from coming into contact with spray mist.</p> <p>Care must be taken to apply material at recommended mil thickness.</p> <p>Box all containers of same color.</p> <p>Do not shake. STIR GENTLY BEFORE USE. Keep containers covered during and after use.</p> <p>Apply uniformly with minimal brushing, rolling or repeated coating.</p>	<p>Clean Up Thinner: Water</p> <p>Clean all equipment immediately after use with clean water.</p> <p><u>MAINTENANCE</u></p> <p>Wait at least four weeks after application before washing. May be cleaned using water and soft cloth or sponge, or mild household general cleaning solution.</p> <p><u>STORAGE & DISPOSAL</u></p> <p>Do not store near drinking water, food or animal feed.</p> <ul style="list-style-type: none"> • Pesticide Storage: Keep containers tightly sealed. Store in a cool, dry place. KEEP FROM FREEZING. • Pesticide Disposal: Dispose of unused product in accordance with applicable federal, state and local government regulations. Contact the state pesticide officer or EPA Hazardous Waste representative. • Container Disposal: Triple rinse and offer for recycling or puncture and dispose of in a sanitary landfill or other procedure in accordance with applicable regulations. <p><u>LIMITED WARRANTY</u></p> <p>Alistagen Corporation and its representatives make no warranties, expressed or implied, concerning this product or its fitness for use beyond the description on the product label. Read all directions carefully and observe all precautions. Read Material Safety Data Sheet for further safety and handling information.</p>	<p>Danger! Corrosive. In severe cases, may cause irreversible eye damage. Wear approved protective eyewear during application (goggles, face shield or safety glasses). Do not allow product to come into contact with eyes. Avoid direct contact with skin while applying.</p> <p>First Aid Have product container or label available when calling a poison control center or physician.</p> <p>Skin Contact – Rinse sensitive skin immediately. Contact a poison control center or physician for treatment advice.</p> <p>Eye Contact – Remove contact lenses. Hold eye open and rinse slowly and gently with clean water for 5 minutes. Continue rinsing until irritation subsides. Contact a poison control center or physician immediately for treatment advice.</p> <p>Ingestion - Contact a poison control center or physician immediately for treatment advice. Promptly drink a large quantity of milk, egg whites or gelatin solution. If not available, drink large quantities of water. Avoid alcohol. DO NOT INDUCE VOMITING.</p> <p>Physician Note: Probable mucosal damage may contraindicate the use of gastric lavage.</p> <p>Environmental Hazards Do not apply directly to water. Do not contaminate water when disposing of equipment, containers, wash water or rinsate.</p>